



FLORIDA DEPARTMENT OF ENVIRONMENTAL PROTECTION
GROUND WATER SAMPLING FIELD LOG SHEET

Watershed Monitoring Section

January 2013

SAMPLING AGENCY: <u>FDEP/8034</u>	FLUWID: <u>AAN3422</u>	OWNER:
STATUS RANDOM ID:	STATION NAME: <u>MSFMW17</u>	PROJECT: <u>MSFNS</u>
LAND SURFACE ELEV.(LSE): <u>69.0</u>	CASING MATERIAL: <u>PVC</u>	TOTAL DEPTH: <u>47</u>
MEASURING POINT ELEV.(MPE): <u>71.8</u>	CASING DIAMETER: <u>4"</u>	

All Times Are: ETZ or CTZ (circle one) Date/Time On Site: 14:08 8-21-13 Date/Time Off Site: 15:00 8-21-13

Field Sheet Completed By: PS WQ Samples Collected By: ME

POTENTIOMETRIC METHOD

(Stickup is MPE - LSE)

Total Depth - (Depth to Water - Stickup) = Water Column Height (*DTW = N/A if not measurable)	Second Reading
<u>47</u> - (<u>35.35</u> - <u>2.8</u>) = <u>14.45</u> ft	<u>14.55</u> ft
DTW - SU = <u>32.55</u> (WCH)	(WCH)

TAPE / CHALK METHOD

Total Depth - ((Held at - Wetted At) - SU) = Water Column Height
1. _____ - ((_____ - _____) - _____) = _____
2. _____ - ((_____ - _____) - _____) = _____
DTW - SU = _____

PURGE METHOD (Check one):

- ☒ 1) 1.5 well volumes and stability ☐ 2) In-place plumbing purge and stability (continuous and intermittently running wells)
☐ 3) More than 1.5 well volumes and stability ☐ 4) Fully dry purge (not recommended)
☐ 5) Purged 5 or more well volumes without stability (explain in comments) ☐ 6) Other (explain in comments)

MINIMUM PURGE VOLUME DETERMINATION

.041 X Diameter X Diameter X Water Column Height X # Well Purge Volumes = Min. Purge Volume (gal.)

.041 X _____ X _____ X _____ X 1.5 = _____

Water Column Height (WCH) X Well Capacity X # Well Purge Volumes = Min. Purge Volume (gal.)

14.55 X 0.65 X 1.5 = 14.18 (gal.)

1 Well Purge Volume: 9.45 (gal.) 1/4 Well Purge Volume: 2.36 (gal.)

Volume of tank (if required to purge): _____ (gal.)

Well Capacity (Gallons per ft): .75" = .02, 1" = .04, 1.25" = .06, 2" = .16, 3" = .37, 4" = .65, 5" = 1.02, 6" = 1.47, 8" = 2.62, 10" = 4.10, 12" = 5.88

Purge Equipment Used: 2" Redi-Flo 2 #1 Sample Equipment Used: 2" Redi-Flo 2 #1
Please include type of pump (peristaltic, submersible, etc.) AND pump ID# (ex. Redi-flo #1, Grundfos #2, etc.)

Minimum Purge Time: (Min. Purge Volume/Purge Rate) 14.18 (min.)

Time Purge Begin: 14:22 (24hr) Time Purge Stop: 14:37 (24hr) Purge Rate: 1 (gal/min)

Total Purge Time: 15 (min.) Total Purge Volume: 15 (gal.)
(Purge rate X Total purge Time)

Time Sampling Begin: 14:38 (24 hr) Time Sampling Stop: 14:45 (24 hr)

AAN3422
PLACE
FLUWID LABEL HERE
(if applicable)

MSFMW17
PLACE
SITE LABEL HERE

PLACE QA/QC LABEL HERE
(if applicable)

QA/QC Sample: N/A Field Blank Equipment Blank Time (24hr): _____
 (Circle One) (Field-cleaned) (Lab-cleaned)
 Equipment Used: _____ Collected by: _____

Well Condition: normal Fuel-Powered Equipment Used? Yes No
 (Circle One)

Placement Depth of Tubing or Pump Intake: 37'

Drawdown Monitored? (Circle One) No (N/A) Yes, no drawdown Yes, drawdown noticed and corrected for
 This is verified by recording depth to water in the Chemical Stability Monitoring section.

Sulfur Odor?: (Circle One) Yes No Color: none

Personnel/Visitors On Site: Mike Eckles / Paul Blair

Weather Conditions: p. cloudy

PRESERVATION INFORMATION ☐ N/A (No samples collected; non-quarterly Trend month, etc.)
 Were all appropriate samples (including QA/QC blanks) preserved within 15 minutes including the following: wet ice (<6°C); nutrient samples with 1 mL sulfuric acid; metal samples with 1 mL nitric acid; ortho-phosphate sample filtered with a .45µm filter; and anion, metal and nutrient samples filtered with a .45µm filter (for Oct. TREND network only) Yes No
 Were all acidified samples verified that the pH was less than 2 SU? Yes No Preserved By: JB
 Preservative Lot #: Sulfuric 126165 Nitric 1113020
 (Please describe any variations to this preservation protocol in the comments section below.)

COMMENTS: (Include any variations from normal preservation protocols; ex. adding more than 1 ml acid, unable to monitor depth to water because..., etc.)

CHEMICAL STABILITY MONITORING										Meter ID# <u>VSI 600XLM #11</u>		Read By: <u>JB</u>	
	Time (24hr.)	Volume Purged (gallons)	Purge Rate (gal/min)	Depth to Water (feet)***	Temp. (°C)	Cond. (µmhos/cm)	DO (%)	DO (mg/L)	pH (SU)	Turbidity (NTU)	Comments		
1	<u>14:32</u>	<u>10</u>	<u>1</u>	<u>35.89</u>	<u>23.7</u>	<u>883</u>	<u>78.0</u>	<u>6.58</u>	<u>7.1</u>	<u>2.68</u>			
2	<u>14:34</u>	<u>12</u>	<u>1</u>	<u>" "</u>	<u>23.8</u>	<u>843</u>	<u>77.9</u>	<u>6.57</u>	<u>7.1</u>	<u>2.21</u>			
3	<u>14:37</u>	<u>15</u>	<u>1</u>	<u>" "</u>	<u>23.8</u>	<u>853</u>	<u>77.9</u>	<u>6.56</u>	<u>7.1</u>	<u>1.17</u>			
4					<u>830</u>								
5													
6													
7													
8													
9													
10													

Stability Criteria: Temp. ± 0.2°C Specific Conductance ± 5.0% of reading DO ≤ 20% pH ± 0.2 SU Turbidity ≤ 20 NTUs

If DO > 20% or Turbidity > 20 NTUs then: DO ± 0.2 mg/L or 10%, whichever is greater and Turbidity ± 5 NTUs or 10%, whichever is greater

*** Depth to Water needs to be documented if well diameter allows room for both tubing/pump and potentiometer. Not applicable to wells with in-place plumbing. If not applicable, please write "N/A" for this column.

Sampler Names: Paul Blair Mike Eckles
 (Please PRINT)
 Sampler Signatures: Paul Blair Mike Eckles

OFFICE USE ONLY
 Reviewed for completion by: _____ Date: _____