



FLORIDA DEPARTMENT OF ENVIRONMENTAL PROTECTION
GROUND WATER SAMPLING FIELD LOG SHEET
Watershed Monitoring Section

January 2013

Newberry Cemetery
PK 3745

SAMPLING AGENCY: <u>FDEP/8034</u>	FLUWID: <u>AAK7015</u>	OWNER:
STATUS RANDOM ID:	STATION NAME:	PROJECT: <u>MSFNS</u>
LAND SURFACE ELEV.(LSE): <u>N/A</u>	CASING MATERIAL: <u>Steel</u>	TOTAL DEPTH: <u>N/A</u>
MEASURING POINT ELEV.(MPE): <u>N/A</u>	CASING DIAMETER: <u>4"</u>	

All Times Are: ETZ or CTZ (circle one) Date/Time On Site: 10:00 8-21-13 Date/Time Off Site: 10:55 8-21-13

Field Sheet Completed By: PB WQ Samples Collected By: ME

POTENTIOMETRIC METHOD

(Stickup is MPE - LSE)

Total Depth - (Depth to Water - Stickup) = Water Column Height (*DTW = N/A if not measurable)	Second Reading
<u>N/A</u> - (<u>N/A</u> - <u> </u>) = <u>1/A</u> ft	<u>N/A</u> ft
DTW - SU = <u> </u> (WCH)	(WCH)

TAPE / CHALK METHOD

Total Depth - ((Held at - Wetted At) - SU) = Water Column Height
1. <u> </u> - ((<u> </u> - <u> </u>) - <u> </u>) = <u> </u>
2. <u> </u> - ((<u> </u> - <u> </u>) - <u> </u>) = <u> </u>
DTW - SU = <u> </u>

PURGE METHOD (Check one):

- ☒ 1) 1.5 well volumes and stability ☒ 2) In-place plumbing purge and stability (continuous and intermittently running wells)
☐ 3) More than 1.5 well volumes and stability ☐ 4) Fully dry purge (not recommended)
☐ 5) Purged 5 or more well volumes without stability (explain in comments) ☐ 6) Other (explain in comments)

MINIMUM PURGE VOLUME DETERMINATION

.041 X Diameter X Diameter X Water Column Height X # Well Purge Volumes = Min. Purge Volume (gal.)

.041 X X X X 1.5 =

Water Column Height (WCH) X Well Capacity X # Well Purge Volumes = Min. Purge Volume (gal.)

 X X 1.5 = (gal.)

1 Well Purge Volume: (gal.)

1/4 Well Purge Volume: (gal.)

Volume of tank (if required to purge): (gal.)

Well Capacity (Gallons per ft): .75" = .02, 1" = .04, 1.25" = .06, 2" = .16, 3" = .37, 4" = .65, 5" = 1.02, 6" = 1.47, 8" = 2.62, 10" = 4.10, 12" = 5.88

Purge Equipment Used: in-place plumbing Sample Equipment Used: in-place plumbing
Please include type of pump (peristaltic, submersible, etc.) AND pump ID# (ex. Redi-flo #1, Grundfos #2, etc.)

Minimum Purge Time: (Min. Purge Volume/Purge Rate) 8 gpm / 15 min / stability (min.)

Time Purge Begin: 10:25 (24hr)

Time Purge Stop: 10:40 (24hr)

Purge Rate: 8 (gal/min)

Total Purge Time: 15 (min.)

Total Purge Volume: 120 (gal.)

(Purge rate X Total purge Time)

Time Sampling Begin: 10:41 (24 hr)

Time Sampling Stop: 10:47 (24 hr)

AAK7015

PLACE
FLUWID LABEL HERE
(if applicable)

PLACE
SITE LABEL HERE

PLACE QA/QC LABEL HERE
(if applicable)

QA/QC Sample: N/A Field Blank Equipment Blank Time (24hr): _____
 (Circle One) (Field-cleaned) (Lab-cleaned)
 Equipment Used: _____ Collected by: _____

Well Condition: normal Fuel-Powered Equipment Used? Yes No (Circle One)

Placement Depth of Tubing or Pump Intake: N/A (in place)

Drawdown Monitored? (Circle One) No (N/A) Yes, no drawdown Yes, drawdown noticed and corrected for
 This is verified by recording depth to water in the Chemical Stability Monitoring section.

Sulfur Odor?: (Circle One) Yes No Color: none

Personnel/Visitors On Site: Mike Eckles / Paul Blair

Weather Conditions: P. cloudy

PRESERVATION INFORMATION ☐ N/A (No samples collected; non-quarterly Trend month, etc.)

Were all appropriate samples (including QA/QC blanks) preserved within 15 minutes including the following: wet ice (<6°C); nutrient samples with 1 mL sulfuric acid; metal samples with 1 mL nitric acid; ortho-phosphate sample filtered with a .45µm filter; and anion, metal and nutrient samples filtered with a .45µm filter (for Oct. TREND network only) Yes No

Were all acidified samples verified that the pH was less than 2 SU? Yes No Preserved By: PB

Preservative Lot #: Sulfuric 126165 Nitric 1113020
 (Please describe any variations to this preservation protocol in the comments section below.)

COMMENTS: (Include any variations from normal preservation protocols; ex. adding more than 1 ml acid, unable to monitor depth to water because..., etc.)

no site name other than FLUID tag. Well located in cemetery

CHEMICAL STABILITY MONITORING				Meter ID# <u>YS1 600XLM #11</u>				Read By: <u>PB</u>			
	Time (24hr.)	Volume Purged (gallons)	Purge Rate (gal/min)	Depth to Water (feet)***	Temp. (°C)	Cond. (µmhos/cm)	DO (%)	DO (mg/L)	pH (SU)	Turbidity (NTU)	Comments
1	10:30	40	8	N/A	23.1	482	75.2	6.46	7.0	1.12	
2	10:35	80	8	" "	23.1	486	75.3	6.47	7.0	1.68	
3	10:40	120	8	" "	23.0	485	75.4	6.46	7.0	0.71	
4											
5											
6											
7											
8											
9											
10											
Stability Criteria: Temp. ± 0.2°C Specific Conductance ± 5.0% of reading DO ≤ 20% pH ± 0.2 SU Turbidity ≤ 20 NTUs If DO > 20% or Turbidity > 20 NTUs then: DO ± 0.2 mg/L or 10%, whichever is greater and Turbidity ± 5 NTUs or 10%, whichever is greater											

*** Depth to Water needs to be documented if well diameter allows room for both tubing/pump and potentiometer. Not applicable to wells with in-place plumbing. If not applicable, please write "N/A" for this column.

Sampler Names: Paul Blair Mike Eckles

Sampler Signatures: Paul Blair Mike Eckles

OFFICE USE ONLY

Reviewed for completion by: _____

Date: _____