



FLORIDA DEPARTMENT OF ENVIRONMENTAL PROTECTION
GROUND WATER SAMPLING FIELD LOG SHEET

Watershed Monitoring Section

January 2013

SAMPLING AGENCY: 8034	FLUWID: AAN3426	OWNER: Troy + Laura Johnson
STATUS RANDOM ID: MSF MW3	STATION NAME: MSF MW3	PROJECT: MSF MW3 1312 SPRS1310
LAND SURFACE ELEV.(LSE):	CASING MATERIAL: PVC	TOTAL DEPTH: 33
MEASURING POINT ELEV.(MPE):	CASING DIAMETER: 4"	

All Times Are: ETZ or CTZ Date/Time On Site: 12/10/13 14:30 Date/Time Off Site: 15:40 12-10-13
(circle one)

Field Sheet Completed By: ME/PB

WQ Samples Collected By: ME

POTENTIOMETRIC METHOD

(Stickup is MPE - LSE)

Total Depth - (Depth to Water - Stickup) = Water Column Height (*DTW = N/A if not measurable) Second Reading
33 - (20.22 - 2.86) = 15.84 ft 15.84 ft
DTW - SU = 17.3610 (WCH) (WCH)

TAPE / CHALK METHOD

Total Depth - ((Held at - Wetted At) - SU) = Water Column Height

1. _____ - ((_____ - _____) - _____) = _____
2. _____ - ((_____ - _____) - _____) = _____
DTW - SU = _____

PURGE METHOD (Check one):

- ☒ 1) 1.5 well volumes and stability ☐ 2) In-place plumbing purge and stability (continuous and intermittently running wells)
☐ 3) More than 1.5 well volumes and stability ☐ 4) Fully dry purge (not recommended)
☐ 5) Purged 5 or more well volumes without stability (explain in comments) ☐ 6) Other (explain in comments)

MINIMUM PURGE VOLUME DETERMINATION

.041 X Diameter X Diameter X Water Column Height X # Well Purge Volumes = Min. Purge Volume (gal.)

.041 X _____ X _____ X _____ X 1.5 = _____

Water Column Height (WCH) X Well Capacity X # Well Purge Volumes = Min. Purge Volume (gal.)

15.84 X 0.65 X 1.5 = 15.44 (gal.)

1 Well Purge Volume: 10.296 (gal.)

1/4 Well Purge Volume: 2.06 (gal.)

Volume of tank (if required to
purge): _____ (gal.)

Well Capacity (Gallons per ft) : .75" = .02, 1" = .04, 1.25" = .06, 2" = .16, 3" = .37, 4" = .65, 5" = 1.02, 6" = 1.47, 8" = 2.62,
10" = 4.10, 12" = 5.88

Purge Equipment Used: Rediflo #1

Sample Equipment Used: Rediflo/Tubing/Flowmeter

Please include type of pump (peristaltic, submersible, etc.) AND pump ID# (ex. Redi-flo #1, Grundfos #2, etc.)

Minimum Purge Time: (Min. Purge Volume/Purge Rate) 15.44 (min.)

Time Purge Begin: 15:07 (24hr)

Time Purge Stop: 15:24 (24hr)

Purge Rate: 1 (gal/min)

Total Purge Time: 17 (min.)

Total Purge Volume: 17 (gal.)

(Purge rate X Total purge Time)

Time Sampling Begin: 15:25 (24 hr)

Time Sampling Stop: 15:30 (24 hr)

AAN3426

PLACE
FLUWID LABEL HERE
(if applicable)

MSF MW3

PLACE
SITE LABEL HERE

MSF MW 1312

PLACE QA/QC LABEL HERE
(if applicable)

QA/QC Sample: N/A Field Blank Equipment Blank Time (24hr): _____
 (Circle One) (Field-cleaned) (Lab-cleaned)
 Equipment Used: _____ Collected by: _____

Well Condition: Normal Fuel-Powered Equipment Used? Yes No
 (Circle One)

Placement Depth of Tubing or Pump Intake: 25'

Drawdown Monitored? (Circle One) No (N/A) Yes no drawdown Yes, drawdown noticed and corrected for
 This is verified by recording depth to water in the Chemical Stability Monitoring section.

Sulfur Odor?: (Circle One) Yes No Color: clear

Personnel/Visitors On Site: Eckles / Blair

Weather Conditions: Clear

PRESERVATION INFORMATION ☐ N/A (No samples collected; non-quarterly Trend month, etc.)

Were all appropriate samples (including QA/QC blanks) preserved within 15 minutes including the following: wet ice (<6°C); nutrient samples with 1 mL sulfuric acid; metal samples with 1 mL nitric acid; ortho-phosphate sample filtered with a .45µm filter; and anion, metal and nutrient samples filtered with a .45µm filter (for Oct. TREND network only) Yes No

Were all acidified samples verified that the pH was less than 2 SU? Yes No Preserved By: PB

Preservative Lot #: Sulfuric 120591 Nitric 1113026
 (Please describe any variations to this preservation protocol in the comments section below.)

COMMENTS: (Include any variations from normal preservation protocols; ex. adding more than 1 ml acid, unable to monitor depth to water because..., etc.)

CHEMICAL STABILITY MONITORING				Meter ID# 957.600 YLM #11				Read By: ME			
	Time (24hr.)	Volume Purged (gallons)	Purge Rate (gal/min)	Depth to Water (feet)***	Temp. (°C)	Cond. (µmhos/cm)	DO (%)	DO (mg/L)	pH (SU)	Turbidity (NTU)	Comments
1	15:18	11	1	20.37	23.9	179	86.9	7.32	9.46 ⁷⁸	1.04	
2	15:21	14	1	"	23.9	181	86.9	7.31	9.43	0.90	
3	15:24	17	1	"	23.9	183	87.3	7.35	9.43	0.78	
4											
5											
6											
7											
8											
9											
10											
Stability Criteria: Temp. ± 0.2°C Specific Conductance ± 5.0% of reading DO ≤ 20% pH ± 0.2 SU Turbidity ≤ 20 NTUs											
If DO > 20% or Turbidity > 20 NTUs then: DO ± 0.2 mg/L or 10%, whichever is greater and Turbidity ± 5 NTUs or 10%, whichever is greater											

*** Depth to Water needs to be documented if well diameter allows room for both tubing/pump and potentiometer. Not applicable to wells with in-place plumbing. If not applicable, please write "N/A" for this column.

Sampler Names: P.M. Blair

Sampler Signatures: P.M. Blair (Please PRINT)

M.A. Eckles

OFFICE USE ONLY

Reviewed for completion by: _____ Date: _____