

QA/QC Sample: N/A (Circle One) Field Blank Equipment Blank  
 (Field-cleaned) (Lab-cleaned)  
 Time (24hr): \_\_\_\_\_  
 Equipment Used: \_\_\_\_\_ Collected by: \_\_\_\_\_

Well Condition: Normal Fuel-Powered Equipment Used? Yes (Circle One) No

Placement Depth of Tubing or Pump Intake: 54'

Drawdown Monitored? (Circle One) No (N/A) Yes, no drawdown Yes, drawdown noticed and corrected for  
 This is verified by recording depth to water in the Chemical Stability Monitoring section.

Sulfur Odor?: (Circle One) Yes No Color: Clear

Personnel/Visitors On Site: Eckles / Blair

Weather Conditions: Clear

Photos Taken? Yes No (indicate why in comments) Micro Land Use? Yes No (indicate why in comments)  
 (Circle One. Required for all Status sites. Required Annually for Trend Sites.) (Circle One. Required for all Status sites. Required Annually for Trend Sites.)

**PRESERVATION INFORMATION** ☐ N/A (No samples collected; non-quarterly Trend month, etc.)

Were all appropriate samples (including QA/QC blanks) preserved within 15 minutes including the following: wet ice  $\pm 6^{\circ}\text{C}$ ; nutrient samples with 1 mL sulfuric acid; metal samples with 1 mL nitric acid; ortho-phosphate sample filtered with a .45 $\mu\text{m}$  filter; and anion, metal and nutrient samples filtered with a .45 $\mu\text{m}$  filter (for Oct. TREND network only) Yes No

Were all acidified samples verified that the pH was less than 2 SU? Yes No Preserved By: ME

Preservative Lot #: Sulfuric 126185 Nitric 1113040  
 (Please describe any variations to this preservation protocol in the comments section below.)

COMMENTS: (Include any variations from normal preservation protocols; ex. adding more than 1 ml acid, unable to monitor depth to water because..., etc.)

| CHEMICAL STABILITY MONITORING |              |                         |                      | Meter ID# <u>YST 600 K/Lm #11</u> |                              |                                              |             | Read By: <u>ME</u> |            |                 |          |
|-------------------------------|--------------|-------------------------|----------------------|-----------------------------------|------------------------------|----------------------------------------------|-------------|--------------------|------------|-----------------|----------|
|                               | Time (24hr.) | Volume Purged (gallons) | Purge Rate (gal/min) | Depth to Water (feet)***          | Temp. ( $^{\circ}\text{C}$ ) | Specific Conductance ( $\mu\text{mhos/cm}$ ) | DO (%)      | DO (mg/L)          | pH (SU)    | Turbidity (NTU) | Comments |
| 1                             | <u>10:50</u> | <u>9</u>                | <u>1</u>             | <u>52.59</u>                      | <u>23.6</u>                  | <u>602</u>                                   | <u>84.7</u> | <u>7.17</u>        | <u>6.7</u> |                 |          |
| 2                             | <u>10:53</u> | <u>12</u>               | <u>1</u>             | <u>52.59</u>                      | <u>23.5</u>                  | <u>603</u>                                   | <u>85.7</u> | <u>7.26</u>        | <u>6.7</u> |                 |          |
| 3                             | <u>10:55</u> | <u>14</u>               | <u>1</u>             | <u>52.89</u>                      | <u>23.5</u>                  | <u>605</u>                                   | <u>86.3</u> | <u>7.31</u>        | <u>6.6</u> |                 |          |
| 4                             |              |                         |                      |                                   |                              |                                              |             |                    |            |                 |          |
| 5                             |              |                         |                      |                                   |                              |                                              |             |                    |            |                 |          |
| 6                             |              |                         |                      |                                   |                              |                                              |             |                    |            |                 |          |
| 7                             |              |                         |                      |                                   |                              |                                              |             |                    |            |                 |          |
| 8                             |              |                         |                      |                                   |                              |                                              |             |                    |            |                 |          |
| 9                             |              |                         |                      |                                   |                              |                                              |             |                    |            |                 |          |
| 10                            |              |                         |                      |                                   |                              |                                              |             |                    |            |                 |          |

Stability Criteria: Temp.  $\pm 0.2^{\circ}\text{C}$  Specific Conductance  $\pm 5.0\%$  of reading DO  $\leq 20\%$  pH  $\pm 0.2\text{SU}$  Turbidity  $\leq 20\text{NTUs}$   
 If DO  $> 20\%$  or Turbidity  $> 20\text{NTUs}$  then: DO  $\pm 0.2\text{mg/L}$  or  $10\%$ , whichever is greater and Turbidity  $\pm 5\text{NTUs}$  or  $10\%$ , whichever is greater

\*\*\* Depth to Water needs to be documented if well diameter allows room for both tubing/pump and potentiometer. Not applicable to wells with in-place plumbing. If not applicable, please write "N/A" for this column.

Sampler Names: M. d. Eckles P. M. Blair  
 (Please PRINT)

Sampler Signatures: \_\_\_\_\_

**OFFICE USE ONLY**  
 Reviewed for completion by: \_\_\_\_\_ Date: \_\_\_\_\_



FLORIDA DEPARTMENT OF ENVIRONMENTAL PROTECTION  
GROUND WATER SAMPLING FIELD LOG SHEET

Watershed Monitoring Section

October 2013

|                                |                          |                       |
|--------------------------------|--------------------------|-----------------------|
| SAMPLING AGENCY: 8034          | FLUWID: AA 7 3414        | OWNER: Destiny Church |
| STATUS RANDOM ID: MSF - MW #14 | STATION NAME: MSF MW #14 | PROJECT: SPRS1410     |
| LAND SURFACE ELEV.(LSE):       | CASING MATERIAL: PVC     | TOTAL DEPTH: 60       |
| MEASURING POINT ELEV.(MPE):    | CASING DIAMETER: 4"      |                       |

All Times Are: (ETZ) or CTZ Date/Time On Site: 6/18/14 10:37 Date/Time Off Site: 6/18/14 11:10  
(circle one)

Field Sheet Completed By: ME WQ Samples Collected By: PB

POTENTIOMETRIC METHOD

(Stickup is MPE - LSE)

|                                                                |                                |                |
|----------------------------------------------------------------|--------------------------------|----------------|
| Total Depth - (Depth to Water - Stickup) = Water Column Height | (*DTW = N/A if not measurable) | Second Reading |
| 60 - (49.38 - 3.02) = 13.64 ft                                 |                                | 13.64 ft       |
| DTW - SU = 46.36                                               | (WCH)                          | (WCH)          |

TAPE / CHALK METHOD

|                                                                  |
|------------------------------------------------------------------|
| Total Depth - ((Held at - Wetted At) - SU) = Water Column Height |
| 1. _____ - ((_____ - _____) - _____) = _____                     |
| 2. _____ - ((_____ - _____) - _____) = _____                     |
| DTW - SU = _____                                                 |

PURGE METHOD (Check one):

- ☒ 1) 1.5 well volumes and stability ☐ 2) In-place plumbing purge and stability (continuous and intermittently running wells)  
☐ 3) More than 1.5 well volumes and stability ☐ 4) Fully dry purge (not recommended)  
☐ 5) Purged 5 or more well volumes without stability (explain in comments) ☐ 6) Other (explain in comments)

MINIMUM PURGE VOLUME DETERMINATION

.041 X Diameter X Diameter X Water Column Height X # Well Purge Volumes = Min. Purge Volume (gal.)  
.041 X \_\_\_\_\_ X \_\_\_\_\_ X 1.5 = \_\_\_\_\_

Water Column Height (WCH) X Gfw (gallons per foot of water) X # Well Purge Volumes = Min. Purge Volume (gal.)

13.64 X 0.65 X 1.5 = 13.30 (gal.)

1 Well Purge Volume: 8.867 (gal.)

1/4 Well Purge Volume: 2.22 (gal.)

Volume of tank (if required to  
purge): \_\_\_\_\_ (gal.)

Well Diameter (inches) → Gfw (Gallons per foot of water): 0.75" → 0.02; 1" → 0.04; 1.25" → 0.06; 2" → 0.16; 3" → 0.37;  
4" → 0.65; 5" → 1.02; 6" → 1.47; 8" → 2.62; 10" → 4.10; 12" → 5.88

Purge Equipment Used: RediFlo II #1

Sample Equipment Used: RediFlo/Tob./Fluvel

Please include type of pump (peristaltic, submersible, etc.) AND pump ID# (ex. Redi-flo #1, Grundfos #2, etc.)

Minimum Purge Time: (Min. Purge Volume/Purge Rate) 13.30 (min.)

Time Purge Begin: 10:41 (24hr)

Time Purge Stop: 10:55 (24hr)

Purge Rate: 1 (gal/min)

Total Purge Time: 14 (min.)

Total Purge Volume: 14 (gal.)

(Purge rate X Total purge Time)

Time Sampling Begin: 10:57 (24 hr)

Time Sampling Stop: 11:00 (24 hr)

PLACE  
FLUWID LABEL HERE  
(if applicable)

PLACE  
SITE LABEL HERE

PLACE QA/QC LABEL HERE  
(if applicable)

MSF MW #14  
SPRS1410