

SITE NAME: 5.2		SITE LOCATION: Spring St	
WELL NO:	SAMPLE ID:	DATE: 2/7/23	

WELL DIAMETER (Inches):	TUBING DIAMETER (Inches):	WELL SCREEN INTERVAL DEPTH: feet to feet	STATIC DEPTH TO WATER (feet):	PURGE PUMP TYPE OR BAILER:
----------------------------	------------------------------	---	----------------------------------	-------------------------------

(Only fill out if applicable)

= (feet - feet) X gallons/foot = gallons

$$= \text{gallons} + (.106 \text{ gallons/foot} \times 24 \text{ feet}) + 0.118 \text{ gallons} = 0.262 \text{ gallons}$$

TOTAL VOLUME
PURGED (gallons): 6.5

[illegible]

WELL CAPACITY (Gallons Per Foot): 0.75" = 0.02; 1" = 0.04; 1.25" = 0.06; 2" = 0.16; 3" = 0.37; 4" = 0.65; 5" = 1.02; 6" = 1.47; 12" = 5.88
TUBING INSIDE DIA. CAPACITY (Gal./Ft.): 1/8" = 0.0006; 3/16" = 0.0014; 1/4" = 0.0026; 5/16" = 0.004; 3/8" = 0.006; 1/2" = 0.010; 5/8" = 0.016

PURGING EQUIPMENT CODES: **B** = Bailer: **BP** = Bladder Pump: **ESP** = Electric Submersible Pump: **PP** = Peristaltic Pump: **O** = Other (Specify)

SAMPLED BY (PRINT) / AFFILIATION: EDER	SAMPLER(S) SIGNATURE(S): [Signature]	SAMPLING INITIATED AT: 9:45	SAMPLING ENDED AT: 9:49
---	---	-----------------------------	-------------------------

SAMPLING
INITIATED AT:

SAMPLING ENDED AT: 9:49

FIELD-FILTERED: Y N
Filtration Equipment Type:

FILTER SIZE: μm

FIELD DECONTAMINATION: PUMP Y

TUBING Y N (replaced)

DUPLICATE: Y ☒

[illegible]

REMARKS:

MATERIAL CODES: AG = Amber Glass; CG = Clear Glass; HDPE = High Density Polyethylene; LDPE = Low Density Polyethylene; PP = Polypropylene;
S = Silicone; T = Teflon; O = Other (Specify)

SAMPLING EQUIPMENT CODES: APP = After (Through) Peristaltic Pump; B = Bailer; BP = Bladder Pump; ESP = Electric Submersible Pump;
RFPP = Reverse Flow Peristaltic Pump; SM = Straw Method (Tubing Gravity Drain); O = Other (Specify)

NOTES: 1. The above do not constitute all of the information required by Chapter 62-160, F.A.C.

2. STABILIZATION CRITERIA FOR RANGE OF VARIATION OF LAST THREE CONSECUTIVE READINGS (SEE FS 2212, SECTION 3)

pH: ± 0.2 units **Temperature:** ± 0.2 °C **Specific Conductance:** $\pm 5\%$ **Dissolved Oxygen:** all readings $\leq 20\%$ saturation (see Table FS 2200-2); optionally, $+0.2$ mg/L or $+10\%$ (whichever is greater) **Turbidity:** all readings < 20 NTU; optionally $+5$ NTU or $+10\%$ (whichever is greater)

Field/WIN ID →



5.2

Location:

Manhole west side of Spring Street north of Romana
and South of Garden

Revision Date: January 2017

SITE NAME: 1.0		SITE LOCATION: Coyle + Main St	
WELL NO:	SAMPLE ID:	DATE: 2.7.23	

WELL DIAMETER (Inches):	TUBING DIAMETER (Inches):	WELL SCREEN INTERVAL DEPTH: feet to feet	STATIC DEPTH TO WATER (feet):	PURGE PUMP TYPE OR BAILER:
----------------------------	------------------------------	---	----------------------------------	-------------------------------

(only fill out if applicable)

$$= (\quad \text{feet} - \quad \text{feet}) \times \quad \text{gallons/foot} = \quad \text{gallons}$$
EQUIPMENT VOUCHER
(only fill out if applicable)
$$= \text{gallons} + (\text{gallons/foot} \times \text{feet}) + \text{gallons} = \text{gallons}$$

INITIAL PUMP OR TUBING
DEPTH IN WELL (feet):

FINAL PUMP OR TUBING
DEPTH IN WELL (feet):

PURGING
INITIATED AT:

PURGING
ENDED AT:

TOTAL VOLUME
PURGED (gallons):

TIME	VOLUME PURGED (gallons)	CUMUL. VOLUME PURGED (gallons)	PURGE RATE (gpm)	DEPTH TO WATER (feet)	pH (standard units)	TEMP. (°C)	COND. (circle units) µmhos/cm or µS/cm	DISSOLVED OXYGEN (circle units) mg/L or % saturation	TURBIDITY (NTUs)	COLOR (describe)	ODOR (describe)
0840	—	—	—	—	7.93	17.7	215.9	4.44 ^{mg/L} 46.2 %	—	Clear	Slight Sewage

WELL CAPACITY (Gallons Per Foot): 0.75" = 0.02; 1" = 0.04; 1.25" = 0.06; 2" = 0.16; 3" = 0.37; 4" = 0.65; 5" = 1.02; 6" = 1.47; 12" = 5.88
TUBING INSIDE DIA. CAPACITY (Gal./Ft.): 1/8" = 0.0006; 3/16" = 0.0014; 1/4" = 0.0026; 5/16" = 0.004; 3/8" = 0.006; 1/2" = 0.010; 5/8" = 0.016

PURGING EQUIPMENT CODES: B = Baller; BP = Bladder Pump; ESP = Electric Submersible Pump; PP = Peristaltic Pump; O = Other (Specify)

SAMPLED BY (PRINT) / AFFILIATION: DEP	SAMPLER(S) SIGNATURE(S): MIL ME [Signature]	SAMPLING INITIATED AT: 8:70	SAMPLING ENDED AT: 8:45
--	--	-----------------------------	-------------------------

PUMP OR TUBING
DEPTH IN WELL (feet):

TUBING MATERIAL CODE: LDPE

SAMPLING INITIATED AT: 8:70

SAMPLING
ENDED AT: 8.48

PUMP OR TUBING
DEPTH IN WELL (feet):

TUBING MATERIAL CODE: LDPE

FIELD-FILTERED: Y 
Filtration Equipment Type:

FILTER SIZE: _____ μm

FIELD DECONTAMINATION: PUMP Y ~~N~~ TUBING Y ~~N~~ (replaced)

DUPLICATE: Y ☒ N

SAMPLE CONTAINER SPECIFICATION

SAMPLE PRESERVATION (including wet ice)

INTENDED

SAMPLING

SAMPLE PUMP

[illegible]

REMARKS:

SURFACE GRAB 451 155077

MATERIAL CODES: AG = Amber Glass; CG = Clear Glass; HDPE = High Density Polyethylene; LDPE = Low Density Polyethylene; PP = Polypropylene; S = Silicone; T = Teflon; O = Other (Specify)

SAMPLING EQUIPMENT CODES: APP = After (Through) Peristaltic Pump; B = Bailer; BP = Bladder Pump; ESP = Electric Submersible Pump;
RFPF = Reverse Flow Peristaltic Pump; SM = Straw Method (Tubing Gravity Drain); O = Other (Specify)

NOTES: 1. The above do not constitute all of the information required by Chapter 62-160, F.A.C.

2. STABILIZATION CRITERIA FOR RANGE OF VARIATION OF LAST THREE CONSECUTIVE READINGS (SEE FS 2212, SECTION 3)

pH: ± 0.2 units **Temperature:** ± 0.2 °C **Specific Conductance:** $\pm 5\%$ **Dissolved Oxygen:** all readings $\leq 20\%$ saturation (see Table FS 2200-2); optionally, ± 0.2 mg/L or $\pm 10\%$ (whichever is greater) **Turbidity:** all readings ≤ 20 NTU; optionally ± 5 NTU or $\pm 10\%$ (whichever is greater)

Field/WIN ID →



1.0

62-160,800 F.A.C.

Location:

Outlet south side of road at Coyle extension and Main Street

Revision Date: January 2017

SITE NAME: 5.3		SITE LOCATION: Spring + Cedar St	
WELL NO:	SAMPLE ID:	DATE: 2/7/23	

[illegible]

SAMPLED BY (PRINT) / AFFILIATION: FDER				SAMPLER(S) SIGNATURE(S): [Signature]			SAMPLING INITIATED AT: 7:15		SAMPLING ENDED AT: 9:18		
PUMP OR TUBING DEPTH IN WELL (feet):				TUBING MATERIAL CODE: HDPE		FIELD-FILTERED: Y Filtration Equipment Type:			FILTER SIZE: _____ µm		
FIELD DECONTAMINATION: PUMP Y (Y)				TUBING Y (N (replaced))			DUPLICATE: Y (N)				
SAMPLE CONTAINER SPECIFICATION				SAMPLE PRESERVATION (including wet ice)			INTENDED ANALYSIS AND/OR METHOD		SAMPLING EQUIPMENT CODE	SAMPLE PUMP FLOW RATE (mL per minute)	
SAMPLE ID CODE	# CONTAINERS	MATERIAL CODE	VOLUME	PRESERVATIVE USED	TOTAL VOL ADDED IN FIELD (mL)	FINAL pH					
5.3	1	HDPE	500	—	—	—	PM A		APP	0.25	
5.3	1	HDPE	500	—	—	—	PCR		APP	0.25	
5.3	1	HDPE	500	—	—	—	Tracers		APP	0.25	
		Class									
REMARKS: Blank & Good 9:05 USE 155077											
MATERIAL CODES: AG = Amber Glass; CG = Clear Glass; HDPE = High Density Polyethylene; LDPE = Low Density Polyethylene; PP = Polypropylene; S = Silicone; T = Teflon; O = Other (Specify)											
SAMPLING EQUIPMENT CODES: APP = After (Through) Peristaltic Pump; RFPF = Reverse Flow Peristaltic Pump; B = Bailor; BP = Bladder Pump; ESP = Electric Submersible Pump; SM = Straw Method (Tubing Gravity Drain); O = Other (Specify)											

Outlet southeast side of road at Spring Street and Cedar Street, in bay