



FLORIDA DEPARTMENT OF Environmental Protection

Bob Martinez Center
2600 Blair Stone Road
Tallahassee, FL 32399-2400

Ron DeSantis
Governor

Jay Collins
Lt. Governor

Alexis A. Lambert
Secretary

July 20, 2026

Via Electronic Mail MLee@TerraSystems.net

Michael Lee, Ph.D.
VP of Research and Development
Terra Systems, Inc.
130 Hickman Road, Suite 1
Claymont, DE 19703

Re: **QRS® (60% Sodium Lactate)**
Innovative Technology Application Acceptance Letter

Dear Dr. Lee:

The Florida Department of Environmental Protection's Division of Waste Management (Division) hereby accepts *QRS® (60 % Sodium Lactate)* for in-situ remediation of groundwater and saturated soil impacted by contaminants of concern.

Enclosure 1 contains regulatory information.

For in-situ injections of QRS® there are underground injection control regulations that must be observed: *QRS® (60% Sodium Lactate)* **must be diluted to at least 3%** by weight prior to injections into the subsurface and other conditions must be followed, as prescribed in Enclosure 1.

For vadose zone remediation, such as soil blending, the underlying groundwater may be affected by the leaching of the QRS® formulation. Although this remediation approach is not subject to the regulatory requirements of Chapters 62-528 and 62-520, Florida Administrative Code (F.A.C.), a regulatory advisory for Remedial Action Plan preparers and reviewers is included in Enclosure 1 for assistance with compliance with Chapters 62-780 and 62-777, F.A.C.

The Florida Department of Environmental Protection (DEP) does not provide endorsement of specific or brand name remediation products or processes; however, it does recognize the need to determine their acceptability from an environmental standpoint with respect to applicable rules and regulations, and the interests of public health safety. Vendors are responsible for marketing their product or process on its merits regarding performance, cost, and safety in comparison to competing alternatives in the marketplace. This acceptance letter shall not be construed as either an approval of the product or a certification of its performance.

Additionally, Department acceptance of any product or process does not imply it has been deemed applicable for any particular cleanup situation, or that it is preferred over other treatment or cleanup

Mr. Michael Lee, Ph.D.
Terra Systems, Inc.
July 20, 2026
Page 2

QRS®

techniques. A site-specific evaluation of applicability should be considered for any product or process, whether conventional or innovative, and adequate site-specific design details must be provided in a Remedial Action Plan.

It is not a requirement that a remediation product or process obtain an acceptance from the Department in order to be proposed for use in a site-specific Remedial Action Plan, but the plan must contain information to show that it meets all applicable and appropriate rules and regulations. For QRS® a copy of this acceptance letter containing regulatory compliance advice should be included in the appendix of each site-specific Remedial Action Plan that proposes its use.

The Department reserves the right to revoke its acceptance of a product or process if any component has been falsely represented.

This acceptance letter is valid for a period of ten (10) years from the issuance date above. At the end of the ten-year period, the acceptance can be renewed subject to an updated review of the product's use and formulation. The purpose of the updated review is to determine if the use conditions and monitoring requirements for this product need to be modified.

If you have any questions, contact Elena Compton at (850) 245-8911, through Mail Station 4535 at the letterhead address, or by e-mail at DWM_Innovative@FloridaDEP.gov.

Sincerely,

Elena Compton, M.S., P.E.
Professional Engineer III
District Support Program, FDEP
850-245-8911

Enclosures: (1) Regulatory Information

ENCLOSURE 1
REGULATORY INFORMATION

QRS®
July 20, 2026

1. Groundwater cleanup standards: The onus shall be on users of QRS® to ensure that all applicable groundwater standards will be met at the time of project completion for the contaminants of concern being remediated, and any byproducts produced as a result of chemical reactions induced or assisted by QRS®. The following chapters of the Florida Administrative Code (F.A.C.) are cited: Chapter 62-550, F.A.C., for primary and secondary water quality standards; Chapter 62-520, F.A.C., for groundwater classes, for groundwater permitting, and for monitoring requirements; Chapter 62-528, F.A.C., for underground injection control, particularly Part V, for Class V, Group 4 aquifer remediation projects; Chapter 62-780, F.A.C., for cleanup criteria, allowance of alternative cleanup target levels and conditional closure requirements; and Chapter 62-777, F.A.C., for cleanup target levels.
2. Injection well permit: Per paragraph 62-528.630(2)(c), F.A.C., the issuance of an enforceable, site-specific Remedial Action Plan Approval Order by the Department for injection-type aquifer remediation constitutes the granting of a Class V injection well construction/clearance permit.
3. Underground Injection Control (UIC): Remedial Action Plans proposing injection-type aquifer remediation shall include the information required by subparagraphs 62-528.630(2)(c)1 through 6, F.A.C., for the purposes of the UIC program. Reviewers of those plans, upon issuance of a Department-enforceable Remedial Action Plan Approval Order, must transmit this information to the UIC program in Tallahassee by submitting a completed copy of the "UIC Notification". The notification for sites that are impacted with contaminants of concern is in the form of a memorandum currently located on the Internet at <https://floridadep.gov/waste/district-business-support/documents/uic-notice-remediation-products>.
4. General information about temporary Zones of Discharge (ZOD): For groundwater remediation, the composition of a fluid to be injected must meet the primary and secondary drinking water standards set forth in Chapter 62-550, F.A.C., and the minimum groundwater criteria of Chapter 62-520, F.A.C. [and Chapter 62-777, F.A.C.], pursuant to UIC paragraph 62-528.600(2)(d), F.A.C. Aquifer remediation products that do not meet these requirements must seek relief from water quality criteria by one of two mechanisms as follows. Permission for a temporary ZOD may be obtained via paragraph 62-520.310(8)(c), F.A.C. If permission for a ZOD cannot be obtained by rule, then it will be necessary to seek a variance from Department rules in accordance with Section 120.542, Florida Statutes.

Paragraph 62-520.310(8)(c), F.A.C., allows for a temporary ZOD for closed-loop re-injection systems, for the prime constituents of the reagents used to remediate site contaminants, and for groundwater secondary standards. In order to obtain permission for a temporary ZOD by rule, a site-specific Remedial Action Plan must indicate: (a) the chemical ingredients of concern in the fluid to be injected that will be present in excess of groundwater standards; (b) the size of the ZOD that is needed; (c) the amount of time that the ZOD will be needed; and (d) a plan for monitoring the injected chemical ingredients of concern.

The size of the temporary ZOD will usually be the injection well radius of influence when the treatment system is a single injection point. For a multiple point system, the ZOD can usually be expressed and illustrated as the total area covered by all the injection points, located side-by-side with overlapping radii of influence.

ENCLOSURE 1
REGULATORY INFORMATION

QRS®
July 20, 2026

5. Upon expiration of the time-period granted for the ZOD by way of paragraph 62-520.310(8)(c), F.A.C., the concentrations of the above referenced analytes must meet their respective groundwater standards or their site-specific background values, whichever is less stringent.

Conditional closure is also allowable provided the closure criteria of Rule 62-780.680, F.A.C., are met and there are no exceedances of a primary standard due to impurities in the product. Note that such conditional closure may require a modification of the size or duration of the ZOD. This modification must be approved in an enforceable order of the department, such as a conditional Site Rehabilitation Completion Order.

6. Site-specific Remedial Action Plans shall describe the volume and concentration of QRS® that will be injected.
7. Specific ZOD information for QRS®:
- a. Prior to injections: QRS® (60% Sodium Lactate) **must be diluted to at least 3%** by weight prior to injections into the aquifer, or 3 parts of QRS® and 97 parts of water by weight.
 - b. Please note: if 100% Sodium Lactate is used, then it must be diluted prior to any injections to 2%.
 - c. Please note: Chapter 62-528, F.A.C, requires that the quality of the fluid (or non-liquid substance) introduced to the sub-surface be compared to the primary and secondary drinking water standards and the minimum criteria for groundwater before it is injected (i.e., before it is diluted by the receiving groundwater). A non-compliance with dilution of QRS® (60% Sodium Lactate) to at least 3% prior to its introduction into aquifer, may result in a violation of primary drinking water standard, secondary drinking standard, or minimum criteria for following analytes:
 - i. Antimony (primary drinking water standard = 6 micrograms per liter [ug/L]) and
 - ii. Arsenic (primary drinking water standard = 10 ug/L).
 - d. The outlined above parameters (**antimony** and **arsenic**) are not the ZOD monitoring parameters - but they should be included in the baseline sampling and then annually following treatment to demonstrate and verify compliance with Chapter 62-528, F.A.C.
 - e. For the ZOD parameters: **sodium** and **pH** shall be monitored.
 - f. If QRS® is proposed to be delivered into the aquifer via injection wells, reviewers of Remedial Action Plans should check the box as shown below when filling out the UIC Notification memorandum:
“☐ ZOD permission by paragraph 62-520.310(8)(c), F.A.C., for reagent chemical species and/or parameter(s) in the fluid to be injected (or re-injected) that exceed secondary groundwater standards. ...”.
 - g. If QRS® is proposed to be delivered into the aquifer by means other than injection wells (for example, most excavations [except by large diameter augers], infiltration galleries, trenches,

ENCLOSURE 1
REGULATORY INFORMATION

QRS®
July 20, 2026

etc.), the UIC Notification memorandum is not required to be filed but monitoring for the UIC parameters is required.

8. Quarterly monitoring should suffice in most cases. Upon expiration of the time period granted for the ZOD by way of paragraph 62-520.310(8)(c), F.A.C., the concentrations of the above referenced analytes must meet their respective groundwater standards or their site-specific background values, whichever is less stringent, or appropriate controls are put in place to allow conditional closure under Rule 62-780.680, F.A.C.
 - i. **Sodium** is a primary drinking water pollutant with the following standard:
Na = 160,000 ug/L and
 - ii. **pH** is a secondary drinking water pollutant with the following standard:
pH = 6.5 – 8.5.
9. Utilization of wells: If a remediation site has sufficient monitoring wells, then the Division of Waste Management has no objection to the use of some existing monitoring wells for the injection of *QRS*. However, no “designated” monitoring well, dedicated to the tracking of remediation progress (by sampling) shall be used to apply *QRS*®. Nor shall wells be used for the injection of *QRS*® as dedicated wells for tracking remediation progress. This will avoid a premature conclusion that the site meets cleanup goals. By making sure that designated tracking wells are not used for treatment, there will be more assurance that the treatment process has permeated the entire site and that it did not remain localized to the area immediately surrounding each injection well.
10. Baseline Sampling: Baseline sampling (prior to any injection) for the ZOD monitoring parameters (and the impurities) is not required but is strongly recommended. The baseline sampling data is very useful for evaluating when the aquifer has returned to the pre-injection conditions. Analyses for **antimony**, **arsenic**, **sodium**, and **pH** must be included in the baseline sampling.
11. Four categories of groundwater monitoring:
 - a. Active remediation monitoring for a cleanup site’s contaminants of concern: During the period of active remediation, groundwater shall be monitored in accordance with the requirements of the approved RAP as set forth in Rule 62-780.700, F.A.C.
 - b. Post Active Remediation Monitoring for a cleanup site’s contaminants of concern: At least one (1) year of quarterly post remediation groundwater monitoring for the contaminants of concern shall be conducted at a minimum of two (2) wells: one located in the area of highest contamination, the other at the downgradient edge of the contamination plume, pursuant to Rule 62-780.750, F.A.C.
 - c. Quarterly monitoring of the UIC zone of discharge: When *QRS*® is utilized, in order to comply with paragraph 62-520.310(8)(c), F.A.C., the ZOD shall be *QRS*® monitored for **sodium** and **pH**.
 - d. Annual monitoring of the UIC zone of discharge must include **antimony**, **arsenic**, **sodium**, and **pH**.

ENCLOSURE 1
REGULATORY INFORMATION

QRS®
July 20, 2026

12. Injection operations:

- a. Avoidance of migration: For injection-type in-situ aquifer remediation projects, injection of QRS® shall be performed in such a way and at such a rate and volume that no migration of QRS® (beyond the ZOD) or the contaminants of concern in the aquifer, or surface water, results, pursuant to subsection 62-528.630(3), F.A.C.
- b. Underground Injection Control operating permit: Although an operating permit is not required for aquifer remediation wells pursuant to paragraphs 62-528.640(1)(b) and (c), F.A.C., since no movement of the contamination plume is expected to accompany the treatment process, the Department requests that the information items listed in paragraph 62-528.640(1)(b), F.A.C., be considered and included in Remedial Action Plan proposals as a matter of good and thorough design practice. Briefly summarized, they are the quality of water in the aquifer, quality of the injected fluid, existing and potential uses of the affected aquifer, and well construction details.

13. Abandonment of wells: Upon issuance of a Site Rehabilitation Completion Order or a declaration of “No Further Action”, injection wells shall be abandoned pursuant to Rule 62-528.645, F.A.C. The Underground Injection Control Section of the Department shall be notified so that the injection wells can be removed from the inventory-tracking list.