

Fla. Power 6" A GF-18

NWPID-127

Sheet 1 of 5



CLIENT Meridith Corp. Date 4/11/80
Well No. GCF-OP/A Project No.
Location: State Florida County Gulf
1/4 1/4 1/4 Sec. T. N E
S W
Logged by J. Price Observer P. Waller
Owner: Florida Power Corp.
Well: GCF-OP/A
Driller: Meridith Corp. Date Drilled:
Surface Elevation: ft. Estimated Above MSL
T.D. Logged 606' T.D. Driller
Hole Dia. 6" From 200' to 606' Dia. From To
Casing I. D. 6" From 0 To 200' Dia. From To
Finish: Open hole Screen Gravel Other
Water Level: ft. Above Below MP, Above Below Land Surface
Yield: Flow gpm Pump gpm
Drawdown: ft. after hours pumping @ gpm
Use: Dom. Stock PS Ind. Irr. Test
Heating or cooling Drainage Disposal Obs.
Water Quality:
Temp. °F; Sp. Cond. ; Iron ppm
Cl⁻ ppm; SO₄²⁻ ppm; Total Hardness ppm
Color Odor Taste
Remarks: Measuring point at top of casing approx. 2' above land surface

- Electric
Gamma Ray
Temperature
Caliper
Fluid Resistivity
Fluid Velocity

Log Scales
Electric Log
SP 40 millivolts/inch
Res. 40 ohm-meters/inch
Res. 20 ohms/inch
Gamma Ray Log
20 Counts/sec/in.
Time Constant 4 sec.
Logging speed 30 FPM
Temperature
70 °F to 80 °F
Logging speed 30 FPM
Fluid Resistivity
2 ohm-meters/inch
@ °F
Fluid Velocity
Counts/min/inch
FPM (continuous)
Q = gpm
Caliper
4 inches to 18 inches
Logging speed 30 FPM
Water Samples
Depths sampled: , , , , ,

GEOPHYSICAL WELL SURVEY

