GF 19

NWFID-128

Sheet 2 of 5

CH2M HILL

- [x] Electric
- [x] Gamma Ray
- [] Temperature
- [] Caliper
- [] Fluid Resistivity
- [] Fluid Velocity

GEOPHYSICAL WELL SURVEY

CLIENT Meridith Corp. Date 4/10/80

Well No. GCF-OD/C Project No

Location: State Florida County Gulf

¼ ¼ ¼Sec T: N S R: E W

Logged by J. Price Observer P. Waller

Owner: Florida Power Corp.

Well: GCF-OD/C

Driller: Meridith Corp. Date Drilled:

Surface Elevation: ft. Estimated Measured Above MSL

T.D. Logged 600' T.D. Driller

Hole Dia. 6" From 260' To 600' Dia. From To

Casing I. D. 6" From 0 To 260' Dia. From To

Finish: Open hole Screen Gravel Other

Water Level: ft. Above Below MP. Above Below Land Surface

Yield: Flow gpm Pump gpm

Drawdown: ft. after hours pumping @ gpm

Use: Dom. Stock PS Ind. Irr. Test Heating or cooling Drainage Disposal Obs.

Water Quality:

Temp. °F; Sp. Cond. ; Iron ppm

Cl ppm; SO_4 ppm; Total Hardness ppm

Color Odor Taste

Log Scales

Electric Log	Fluid Resistivity
SP 40 millivolts/inch Res. 40 ohm-meters/inch Res. 20 ohms/inch	2 ohm-meters/inch @ °F
Gamma Ray Log	**Fluid Velocity**
20 Counts/sec/in. Time Constant 4 sec. Logging speed 30 FPM	Counts/min/inch FPM (continuous) Q = gpm
Temperature	**Caliper**
70 °F to 80 °F Logging speed 30 FPM	4 inches to 18 inches Logging speed 30 FPM

Water Samples

Depths sampled: , , , , ,

CH2M HILL
Water Resources Division
P.O. Box 1647
Gainesville, Florida 32602
(904) 377-2442

Remarks: Measuring point at top of casing approx. 2' above land surface.

FE 1029

