



Florida Department of Environmental Protection

Bob Martinez Center
2600 Blair Stone Road
Tallahassee, Florida 32399-2400

Charlie Crist
Governor

Jeff Kottkamp
Lt. Governor

Michael W. Sole
Secretary

April 11, 2007

Mr. Randy Melton
Chair, Solid Waste Subcommittee
Florida Electric Power Coordinating Group, Inc.
1408 North Westshore Boulevard, Suite 1002
Tampa, Florida 33607-4512

APR 23 2007

Dear Mr. Melton:

I am pleased to acknowledge the *Heavy Fuel Oil Discharge Response Actions* protocol, dated April 2007, as an acceptable procedure for meeting the requirements of Rule 62-780.550, Florida Administrative Code *De Minimis Discharges*, when responding to heavy fuel oil discharges. The protocol is the product of a cooperative effort by the Florida Electric Power Coordinating Group and the Division of Waste Management to establish guidance for use by electric utility responders and Department employees.

Copies of this letter and the protocol are being provided to the Department's District Waste Program Administrators and to the Bureau of Emergency Response for their information and use. Please contact Doug Jones, Chief of the Bureau of Waste Cleanup, at (850) 245-8930 if you have any comments or questions.

Sincerely,

Mary Jean Yon, Director
Division of Waste Management

MJY/djr

cc: Phil Wieczynski, Chief, Bureau of Emergency Response
Waste Program Administrators

HEAVY FUEL OIL DISCHARGE RESPONSE ACTIONS

Background

Heavy fuel oil is not a petroleum product as defined in Section 376.301, F.S. Heavy fuel oil includes American Society for Testing and Materials (ASTM) grades number 5 and number 6 residual oils, and intermediate fuel oils used for marine bunkering with a viscosity of 30 and higher. No. 6 fuel oil is far more common than no. 5, and is the principal fuel used by oil-fired power plants. Thus "heavy fuel oil" is frequently used as a synonym for no. 6 residual oil. Heavy fuel oil is a highly viscous oil that has a low propensity to flow. When discharged, it usually results in visual staining of the top 3 to 4 inches of soil in the vicinity of the discharge. The response actions proposed by the Florida Electric Power Coordinating Group, Inc. (FCG) and its member electric utilities takes into consideration the fuel's high viscosity, low propensity to flow, and the staining associated with a discharge.

Applicability

The response actions provided below apply to discharges of heavy fuel oil to a pervious surface. It does not apply to discharges of heavy fuel oil being addressed pursuant to the Clean Water Act. Heavy oil discharged onto impervious surfaces will be recovered. Adherence to this protocol, such that the heavy fuel oil discharge is remediated within 30 days, constitutes compliance with the provisions of Rule 62-780.550, F.A.C. In responding to heavy oil discharges, including those into or near waters of the state, FCG member electric utilities will also comply with all other applicable laws and rules, including applicable notification requirements.

Response Actions

Heavy oil discharge response actions include two types of discharge categories: a new discharge and an existing discharge. A new discharge is defined as a discharge that is known to have occurred within the past 48 hours. An existing discharge is any other heavy oil discharge.

Response actions will be completed within 30 days of discovery of a new or existing discharge. To the extent response actions are not completed within that timeframe, the electric utility will contact the local county storage tank program office or Department of Environmental Protection (Department) district office to develop an appropriate discharge response in accordance with Chapter 62-780, F.A.C.

A. New Discharge Response Protocol

1. New Discharge Not Resulting in Contact with Groundwater

The response actions for a new discharge of any quantity where the discharge did not result in contact with groundwater will be initiated within 48 hours after discovery. Once the source of the discharge is abated or otherwise secured, FCG members will initiate response actions, which include immediate measures to control and abate the discharge.

Soil impacted by heavy fuel oil will be excavated through visual delineation of stained soil. This is typically done using shovels, a backhoe, a track hoe or other appropriate equipment. All visible traces of the heavy oil in the soil will be removed, including a one foot lateral and vertical buffer, unless prevented by a physical obstacle such as a storage tank, building, etc. Excavated soil will be stockpiled on visqueen or other similar impervious material until loaded into 55 gallon drums, roll-off dumpsters or similar containers. Excavated soil will be secured in a manner that prevents human exposure to contaminated soil and prevents soil exposure to precipitation that may cause surface runoff. All excavated soil will be disposed of or treated within 60 days of completion of field activities in accordance with applicable local, state, and federal regulations. Applicable disposal or treatment documents will be obtained.

2. New Discharge Resulting in Contact With Groundwater

The response actions for a new discharge of any quantity that resulted in contact with groundwater will be initiated within 48 hours after discovery. Once the source of the discharge is abated or otherwise secured, FCG members will initiate response actions, which include immediate measures to control and abate the discharge.

In accordance with paragraph C. below, if a new discharge resulted in contact with groundwater confirmatory laboratory analysis will be conducted of the groundwater to ensure that levels of Polycyclic Aromatic Hydrocarbons (PAHs) applicable to heavy fuel oil as provided in Table A are below the corresponding groundwater cleanup target levels for those PAH constituents in Chapter 62-777, F.A.C., or alternative target levels agreed to with the Department.

To the extent such removal cannot be completed within 30 days, the electric utility will contact the relevant Department district office to develop an appropriate discharge response in accordance with Chapter 62-780, F.A.C.

B. Existing Discharge Response Protocol

The response actions for an existing discharge will be initiated as soon as possible after discovery, but no later than 7 days after discovery.

If the discharge is 25 gallons or less and did not result in contact with groundwater, the response protocol for new discharges in paragraph A.1. will be followed.

If the discharge is 25 gallons or less and resulted in contact with groundwater, the response protocol for new discharges will be followed. Also, in accordance with paragraph C. below, potential groundwater impacts will be addressed.

If the discharge is greater than 25 gallons, or resulted in contact with groundwater (see paragraph C. below), all visible traces of the heavy fuel oil in the soil will be recovered including a one foot lateral and vertical buffer as provided in Section A above and confirmatory laboratory analysis of one composite sample of soil from the bottom of the excavation (unless the bottom is below the water table) and the walls or perimeter of the excavation will be conducted to ensure that all impacted soil has been removed. Also, where the existing discharge resulted in contact with groundwater, the provisions of paragraph C. shall be followed.

Verification cleanup of the soil will be confirmed by ensuring that levels of PAHs applicable to heavy fuel oil as provided in Table A are less than the lower of the direct exposure or leachability soil cleanup target levels for those PAH constituents, or other alternative target levels agreed to with the Department. Removal will continue until applicable PAH constituent levels are below the aforementioned concentrations, unless prevented by a physical obstacle as previously mentioned.

To the extent such removal cannot be completed within 30 days, the electric utility will contact the relevant Department district office to develop an appropriate discharge response in accordance with Chapter 62-780, F.A.C.

C. Groundwater Contact

Heavy fuel oil removal activities in groundwater may include but are not be limited to the use of:

- a. Absorbent pads or booms;
- b. Pumps (skimmer, diaphragm, centrifugal, etc.) with mechanical, electrical or hand-bailed purging operations;
- c. Hand or mechanical bailing;
- d. Fluid vacuum techniques; or
- e. Other applicable techniques or technologies.

Recovered heavy fuel oil will either be burned for energy recovery or disposed of or treated in accordance with applicable local, state, and federal regulations.

If a new or existing discharge resulted in contact with groundwater, after heavy fuel oil removal activities in groundwater have been completed, confirmatory laboratory analysis will be conducted to ensure that PAH levels applicable to heavy fuel oil as provided in Table A are below the applicable groundwater cleanup target levels for PAH

constituents in Chapter 62-777, F.A.C., or alternative target levels agreed to with the Department.

D. Documentation

The attached form will be completed by electric utilities for each discharge of heavy fuel oil on a pervious surface and kept on file for a period of five years and made available to the Department upon request.

Table A -PAH Constituents Applicable to Heavy Fuel Oil

Phenanthrene
Anthracene
Fluoranthene
Benz(a)anthracene
Benzo(b)fluoranthene
Benzo(k)fluoranthene
Benzo(a)pyrene
Chrysene
Indeno(1, 2, 3 - cd)pyrene

Summary Document for Heavy Fuel Oil Discharge (on a pervious surface)

Location(s) of Spill (street address of discharge, if known, facility name and narrative description or illustration indicating where discharge occurred)	
Date of Spill	
Type of Product Discharged	
Volume of Product Discharged (in gallons)	
Volume of Free Product Recovered (in gallons)	
Volume of contaminated soil excavated (tons or cubic yards)	
Disposal or recycling methods for free product	
Disposal or recycling methods for excavated soil	
Disposal methods for other contaminated media or investigative related waste	
A site map or sketch showing locations(s) of free product recovered and the area of soil removed.	
Narrative description or illustrations of the approximate dimensions of the excavation – length, width and depth (all dimensions to be provided in feet)	
Documentation confirming the proper treatment and/or disposal of the free product or contaminated soil. (Attach manifests to report)	
Narrative description or illustration of where samples were taken, screening methods used and analytical results. (Attach to report)	
Other applicable information such as a description of any physical obstacles, if any, preventing complete removal.	

Appendix 1

No. 6 Fuel Oil-PAH Analysis and Spill Response Recommendations

PAHs are ubiquitous in the environment, forming whenever organic substances are exposed to high temperatures. They can be broadly separated into three categories: biogenic (formed from natural biological processes including diagenesis); petrogenic (primarily associated with crude oil and natural oil seeps); and pyrogenic (formed in high heat or combustion processes, including incomplete combustion of fuels). PAHs derived from all three categories are likely to be found as contaminants in soils, particularly in urban or industrial areas, but also, for example, in areas where wood-burning stoves (biogenic) and high-volume vehicular traffic (pyrogenic) are present.

Petrogenic PAHs are characterized by low molecular weight compounds with 2 or 3 aromatic rings (i.e., six-carbon fused benzene rings) with a predominance of alkyl substitution (predominantly methyl groups attached to the ring structures). Conversely, pyrogenic PAHs are characterized by high molecular weight compounds typically with 4 to 7 aromatic rings, and much less alkyl substitution. An important toxicological distinction between the two categories is that all known carcinogenic PAHs fall into the high molecular weight, or pyrogenic, category. Atmospheric transport from point sources and the ever-increasing volume of mobile sources ensures the presence of pyrogenic PAHs in nearly all soils in the U.S. and elsewhere in the developed world.

Number (No.) 6 fuel oil, also known as Bunker C fuel, is a refinery by-product, principally the residue of processes in which light and medium crude oils are fractionally distilled and processed to produce gasoline, diesel fuel, and other products. Although derived from a predominately petrogenic source, No. 6 fuel oil may be substantially enriched in 3 to 5-ring PAHs formed in a number of high-temperature petroleum refining processes including catalytic and steam cracking, vacuum distillation, hydrodesulfurization, etc. PAHs in the high-viscosity residuum of the refining process are primarily petrogenic in origin; however, when necessary, low-viscosity blending stocks from the refining operations are blended with residuum to reduce viscosity and improve flowability. This occasional practice has the potential to introduce high-molecular weight pyrogenic PAHs in quantities that are both unpredictable and batch-specific, although the actual concentrations are low. This, along with the petrogenic PAH variability in parent crudes, are why PAH fingerprinting can be used to identify specific sources of fuel oil spills.

To develop a coherent approach to assessing risk from PAHs associated with a spill of residual fuel oil, as well as recommended cleanup criteria, all regulated PAH compounds have been compiled in Table 1. Those not found to be present in No. 6 fuel oil are shaded and all are compared with regulatory endpoints for cleanup action. Composition data for No. 6 fuel oil was compiled by the Total Petroleum Hydrocarbon Criteria Working Group (Potter and Simmons 1998). Data are presented as weight percentages for all fuel constituents reported from a comprehensive search of the literature, and from government, military and oil industry sources.

It is reasonable to assume that any PAHs with maximum reported levels less than 0.02 wt % in No. 6 fuel oil are unlikely to be present at detectable levels in soil or groundwater samples following a fuel spill. That is to say, if these PAHs are detected they would either be at a de minimis level or derived from a source other than a heavy fuel oil spill, given the plethora of potential PAH sources described above. If this assumption is accepted, only the following PAHs found in soils subjected to a No. 6 fuel oil spill should be considered to be derived from that spill:

Phenanthrene
Anthracene
Fluoranthene
Benz(a)anthracene

Chrysene
Benzo(b)fluoranthene
Benzo(k)fluoranthene

The threshold of 0.02 wt % eliminates inclusion of naphthalene; the remainder of PAHs reported to be present in fuel oil No. 6 (see Table 1) are less abundant in fuel oil #6 than naphthalene. (Some, like benzo(a)pyrene [reported only once in fuel oil No. 6], are an order of magnitude less abundant than naphthalene.) Naphthalene is the most soluble of binuclear aromatics, and orders of magnitude more soluble than PAHs with 3 or 4 aromatic rings. This is further justification for not including naphthalene in the above list since solubility is a major factor in determining the rate of biodegradation.

For decisions on remediation of PAHs in the environment it is also important to consider bioavailability. PAH bioavailability will not be discussed further here, but considerable literature information is available (e.g., National Research Council 2003, Stroo et al. 2005).

Recommendations

For response activities related to a No. 6 fuel oil spill to soil and/or groundwater, it is recommended, with respect to PAHs, to compare only the following PAHs and their respective regulatory criteria.

Phenanthrene
Anthracene
Fluoranthene
Benz(a)anthracene
Chrysene
Benzo(b)fluoranthene
Benzo(k)fluoranthene

Bibliography

The following references were used in the development of this Appendix.

API. 1994. Transport and Fate of Non-BTEX Petroleum Chemicals in Soils and Groundwater. API Publication number 4593, American Petroleum Institute, Washington, D.C.

Davis, Jay. 2005. PAHs in the Estuary. San Francisco Bay Institute Regional Monitoring Program, http://www.sfei.org/rmp/rmp_news/RMP_News_vol_2_issue_2.pdf

ERT2 Multimedia Training Tools. 2005. Advanced Chemical Fingerprinting. <http://www.ert2.org/chemicalfingerprinting/printfriendly.aspx>

Massachusetts Department of Environmental Protection. 2005. Polycyclic Aromatic Hydrocarbons. <http://www.mass.gov/dep/toxics/pahs.htm>

National Research Council. 2003. Current Use of Bioavailability in the Management of Contaminated Soil and Sediment, pp. 52-118. In: NRC. 2003. Bioavailability of Contaminants in Soils and Sediments: Processes, Tools, and Applications. 420 pp. National Academies Press, Washington D.C.

Neff, J.M., S.A. Stout and D.G. Gunster. 2005. Ecological risk assessment of polycyclic aromatic hydrocarbons in sediments: identifying sources and ecological hazard. Integrated Environmental Assessment and Management, 1(1):22-33.

Potter, Thomas L. and Kathleen E. Simmons. 1998. Composition of Petroleum Mixtures. Total Petroleum Hydrocarbon Criteria Working Group Series, Volume 2. Amherst Scientific Publishers, Amherst, Massachusetts.

Stroo, H.F. et al. 2005. Improving risk assessments for manufactured gas plant soils by measuring PAH availability. Integrated Environmental Assessment and Management, 1(3):259-266.

Table 1. Compilation of Regulated PAHs, Occurrence in No. 6 Fuel Oil, and Regulatory Characterization and Limits for Spills to Soil in Florida

Priority Pollutants PAHs ¹ (number of aromatic rings)	Reported wt % in No. 6 Fuel Oil ² (avg. and range)	USEPA Carcinogeni c Potential ³	Florida Ground- water CTLs (ug/L)	Florida Soil CTLs – Res/CI (mg/kg) ⁴
Naphthalene ⁵ (2)	4.2E-3 2.1E-4 – 1.5E-2	N/C	14	55 / 300
1-Methylnaphthalene (2)	N/R ⁶	N/A	28	200 / 1800
2-Methylnaphthalene (2)	N/R	N/C	28	210 / 2100
Acenaphthylene (2)	N/R	N/C	210	1800 / 20,000
Acenaphthene (2)	N/R	N/A	20	2400 / 20,000
Fluorene (2)	N/R	N/A	280	2600 / 33,000
Phenanthrene (3)	2.1E-2 2.1E-3 – 4.8E-2	N/C	210	2,200 / 36,000
Anthracene (3)	5.0E-3	N/C	2100	21,000 / 300,000
Fluoranthene (3)	2.4E-2	N/C	280	3200 / 59,000
Pyrene (4)	2.3E-3	N/C	210	2400 / 45,000
Benz(a)anthracene (4)	5.5E-2 2.9E-3 – 1.5E-1	B2	0.05	Calculate based on TEF of 0.1 ⁷
Chrysene (4)	6.9E-2 2.9E-3 - 3.1E-1	B2	4.8	Calculate based on TEF of 0.001
Benzo(b)fluoranthene (4)	4.4E-2	B2	0.05	Calculate based on TEF of 0.1
Benzo(k)fluoranthene (4)	4.4E-2	B2	0.5	Calculate based on TEF of 0.01
Benzo(a)pyrene (5)	4.4E-3	B2	0.2	0.1 / 0.7 (TEF of 1)
Dibenz(a,h)anthracene (5)	N/R	B2	0.005	Calculate based on TEF of 1.0
Benzo(g,h,i)perylene (6)	N/R	N/A	210	2500 / 52,000
Indeno(1,2,3-cd)pyrene (5)	1.0E-2	B2	0.05	Calculate based on TEF of 0.1

1. Includes all reported constituents of No. 6 fuel oil (unshaded) that also are listed in Chapter 62-777 SCTLs.
2. Total Petroleum Hydrocarbon Criteria Working Group. Vol. 2, Composition of Petroleum Mixtures.
3. B2 – probable human carcinogen; N/C – not classifiable; N/A – not available
4. Chapter 62-777, F. A. C. Contaminant Cleanup Target Levels, Risk Impact Statement Section 120.81(6), Florida Statutes (F. S.). Residential and Commercial Industrial CTLs presented.
5. Naphthalene, although included in the Priority Pollutant list, is a di-aromatic and generally not considered in the same group as polynuclear aromatic hydrocarbons.
6. N/R (shaded) = Not reported in literature as occurring in No. 6 Fuel Oil.
7. For applicable PAHs, benz(a)pyrene equivalent concentrations are calculated as the sum of the individual PAH concentration times its toxic equivalency factor (TEF). This concentration should then be compared with the benz(a)pyrene SCTL.